




RDS350

ROTARY DRILL HEAD

TEI Rock Drills manufactures robust hydraulic rotary heads designed for smooth operation and simple maintenance in rotary drilling applications such as soil nailing and micropile operations. Our RDS heads go through the same bench testing procedure prior to delivery as our patented hydraulic drifters. TEI is a preferred replacement rotary drill head in the industry for outperforming the competition.



ROTARY DRILL HEAD



ROTATION SPECIFICATIONS

	U.S.	Metric
ROTATION TORQUE	2000 lbf-ft	2712 Nm
ROTATION FLOW	20 gpm	76 lpm
FLUSH SHAFT ID	1"	25 mm
ROTATION PRESSURE	3000 psi	207 bar
WEIGHT	122 lb	55 kg
SPEED	239 rpm	

OUTPUT THREADS

2 3/8" API M/F, 3 1/2" API M/F, 1 5/8" AUGER HEX



800.777.3745 | 970.249.1515 | WWW.TEIROCKDRILLS.COM

Specifications subject to change without notice.
TEI technical specifications consider a 40% hydraulic power loss.



QUALITY POLICY
CONTINUAL IMPROVEMENT OF CUSTOMER VALUE THROUGH
INNOVATION, EFFICIENCY AND INTEGRITY

TEI08.027.B
REV 02/03/2021